


*THERMAL/THERMAL TRANSFER BAR CODE PRINTER*

# **RING 4012PLM+**



## **LOW COST INDUSTRIAL PRINTER**

- HIGH PERFORMANCE, RELIABLE, AND DURABLE
- RIDGED STEEL CABINET
- 300DPI, 152MM/SEC
- SMALL FOOTPRINT – 225MM(W) X 260MM(D)
- 203MM O.D. SUPPLY ROLL CAPACITY
- 32BIT RISC CPU
- PEEL OFF MODUL COMES STANDARD
- BARTENDER ULTRA LITE PLUS
- VARIOUS OPTION

## RING 4012PLM+ SPECIFICATIONS

### PRINT METHOD

- Thermal Transfer/Direct Thermal
- Harmonic (History Control Print head)

### DOT RESOLUTION

- 300 DPI / 11.8 Dot per mm

### PRINT SPEED

- 1" - 6"/sec. (15 mm – 152 mm/sec.)

### PRINT WIDTH

- 4.25" / 106.0 mm

### PRINT LENGTH

- 27.5" / 700-mm

### MEMORY

- 8MB SDRAM

### MEDIA TYPE

- Die cut labels
- Butt cut labels tags
- Tag stock
- Roll stock (continuous s/o die cuts)
- Fan Fold

### MEDIA WIDTH

- 4.5"/116 mm

### MEDIA THICKNESS

- .0025" to .0100" / .0635 mm to .254 mm

### SUPPLY ROLL CAPACITY

- 8" /203 mm maximum diameter

### RIBBON ROLL CAPACITY

- 2.95" / 75 mm maximum diameter

### CABINET

- All steel cabinet

### LCD DISPLAY

- 2 lines by 8 characters (Alpha / Numeric)
- Back Light

### SENSORS

- Ribbon sensor (Reflective method)
- Label sensor (Transmit method)
- Media Home position sensor (Transmit-Auto calibration method)

### ERROR INDICATORS

- Label / Ribbon empty
- Head open
- Communication
- Grammatical
- Parameter (Each error is notified by buzzer and LCD)

### BAR CODE

- Code 39, Code 93, Code 128, NW7, 2 of 5 (Industrial, Matrix and interleaved), EAN-JAN 13/8, UPC-A/E, EAN128 QR Code, PDF417, Data Matrix, Maxi Code, RSS

### FONTS-CHARACTER SIZE IN DOTS

- 8 Character Sets (Alpha/Numeric and symbols) 8\*8, 12\*12, 16\*16, 16\*24, 24\*24, 24\*26, 32\*40, 48\*60  
Expansion is 1-10 and 16 times (Both directions)
- 5-OCRB Character Sets (4 Numeric and 1 Alpha/Numeric)  
Numeric – 16\*18, 24\*27, 32\*36 and 40\*45  
Alpha/Numeric – 32\*32  
NOTE : Should Not Expand  
Scalable Smooth Fonts  
32-720 Dot width  
32-720 Dot length  
Italic Slant Programmable 10, 15 and 20 degrees. NOTE : 8-31 Dots printing is available but must be matched properly with speed and media
- Down loadable font

### PRINTING MODES & FUNCTIONS

- Peel off, Tear off (demand type) with label back feed for top of label printing.
- Bach printing (strip-for continuous printing of labels. Can be used with optional External Rewinder)
- Butt cut label printing (Requires optional back side mark sensor)

### PROGRAMMING LANGUAGE FEATURES

- Advanced Label marking Language-ALL
- ALL commands are all ASCII characters. This allows flexibility with many environments and platforms
- Easy to program and format printing areas
- Pixel programming allows expanded area of up to 4 times
- Four direction print rotation (0, 90, 180 & 270 degrees)
- Reverse print and area fill in
- Mirror print
- Half Tones
- Lines, dotted lines, angle lines and boxes
- Bit image data transfer and printing
- Down loadable graphics, text, font and formats to optional memory card
- Character Set (Code page)table
- Serializing (Numeric)
- Communication and print functions
- RLE data compression
- Graphic supported AIM, AIX, BMP, PCX (Monochrome only)

### ADJUSTABLE PRINT FUNCTIONS SELECTABLE TROUGH FRONT PANEL OR BY SOFTWARE

- Print Speed / Energy Settings
- Print Density
- Label Print Position
- Cutting Position
- Thermal Transfer / Direct Thermal
- Test Printing
- Ready / Pause

### COMMUNICATION INTERFACE- SELECTABLE THROUGH FRONT PANEL OR BY SOFTWARE

- Parallel
- RS-232 / to 115,200 baud rate  
Line Control-RS-CS, XON-XOFF, ER-DR  
Stop Bits  
Parity  
Data length

### POWER SOURCE

- Multiple Power Supply  
Industrial Standard  
115 volts +-10% AC 50/60 HZ  
240 volts +-10% AC 50/60 HZ  
Built to UL/CSA safety standard  
and FCC emissions standards.

### ENVIRONMENTAL

- Operating temperature  
41 to 104 Fahrenheit / 5 to 40  
Centigrade
- Relative humidity below 85%  
Non-condensing
- Ventilation : Air Movement
- Dust : Non-Conducting, Non-Corrosive

### OPTIONS

- Cutter(guillotine)
- Cutter(non stop rotary)
- Verifier
- External Label Stocker
- 8MB Flash memory
- USB Interface
- LAN Interface  
100 Base -TX/10Base-T  
(TCP/IP Protocol)

### SOFTWARE

- Bartender Ultra Lite Plus
- Windows Drivers

### DIMENSIONS

- 8.9"W\*11.8"H\*10.25"D  
225mmW\*300mmH\*260mmD

### WEIGHT

- 20 lb / 9 kg

### THE ABOVE IS FOR INFORMATION ONLY.

Autonics Company limited reserves the right to change specifications without notice.

**Autonics Co., Ltd.**

4-14-26 Shimomuneoka Shiki-shi  
Saitama 3530008 Japan  
www.ringprinter.com



4012PLM+0605